



CLB C8102-h Local Controller

PRODUCT SHEET

## C8102 Local Controller

### Application and scalability

The controller comes in two shapes / forms: built in a hardware casing (C8102-h) and as a PCB card (C8102-r). The durable and robust design of the casing enables it to be installed locally, for example above suspended ceilings or in fuse boxes. The PCB card type is specifically designed to be installed in 19" racks situated at a central location, for example in technical rooms or cabinets. A typical 19" rack (3 HE) can hold up to 14 C8102-r units.

Two busses with modules can be connected to a single controller covering a distance up to 200 meter (2 x max 100m<sup>1</sup>). The controller and modules are designed to deliver reliable quality across these distances. A single controller can hold up to 60 modules (30 per bus). Each bus string can hold up to 15 modules of the same type.

### Reliability

CLB's controller and modules are developed and manufactured in compliance with ISO 13485, a strict quality standard for medical devices. When applied to the manufacturing process, ISO 13485 certification helps ensure strict quality assurance criteria on every aspect of production, resulting in a tightly controlled manufacturing system that reduces the likelihood of non-conforming products. This provides consistency in product quality and provides a solid basis for greater reliability in device safety and performance.

### System surveillance

The CLB C8102 local controller continuously monitors all modules. When a module is disconnected, disabled or malfunctioning, a warning message is shown to alert an operator or system administrator. The local controller also incorporates a self-monitoring system that can ultimately automatically trigger a controller reboot when an error has caused the local controller to stall.

### Use of existing (standardized) infrastructure

Modules are connected via CAT5 cables to the C8102 controller in two bus strings. In many cases, the existing infrastructure of CAT cables can be used to connect the devices and set-up the system.

### Ease of installation and management

After a simple basic training course, technicians are capable of installing the hardware and checking connection integrity. Module settings are stored on the controller itself. As a result, replacing any module is child's play: simply replace the module (with the address dial set to the same position) and the settings are automatically updated and the system is restored.

### Remote updates


The controller and module firmware can be updated remotely. Besides saving time and reducing maintenance costs, remote updating also increases safety as the system is more likely to have the latest firmware installed.

<sup>1</sup>Depending on number of modules. Please refer to the CLB system installation guide for further details.

## MODELS




CLB C8102-h Local Controller



CLB C8102-r Local Controller

## SYSTEM DIAGRAM



## TECHNICAL SPECIFICATIONS

<b>Dimensions (mm)</b>	h: 164 x 111 x 31 r: 160 x 128.5 (3U) x 30 (6HP)	<b>Connections</b>	2x RJ45 (CAN bus) 1x RJ45 (PoE, PoE+)
<b>Housing</b>	Casing (h) or rack-mount (i)		3x phoenix screws (error relay)
<b>Material</b>	Steel	<b>Protection class</b>	IP30 (when mounted)
<b>LEDs</b>	Green, yellow	<b>Approvals</b>	CE
<b>Buttons</b>	1	<b>Product standards</b>	NEN-EN-IEC 60601-1:2006 NEN-EN-IEC 60601-1-2:2007 NEN-IEC 60601-1-8:2007
<b>Power supply</b>	PoE (IEEE 802.3af) PoE+ (IEEE 802.3at)	<b>Product regulations</b>	93/42/EEC concerning medical devices (14 June 1993)
<b>Supply voltage</b>	24 Vdc		
<b>Power consumption</b>	12.95 - 25.5W		
<b>Operating temperature</b>	0 °C to 40 °C		
<b>Operating humidity (RH)</b>	10% - 95% NC		
<b>Storage temperature</b>	0 °C to 65 °C		
<b>Storage humidity (RH)</b>	10% - 95% NC		

Document ID C8102-1709 | Subject to change without prior notice.